

Total Dose Radiation Test Report
MSK7010-3.3HRH
10W RAD HARD DC TO DC CONVERTER

October 11, 2018 (HDR TID, 1st Test)

B. Horton
F. Freytag

Anaren, Inc – MSK Products

I. Introduction:

The total dose radiation test plan for the MSK7010-3.3HRH was developed to qualify the devices as Radiation Hardened to 100krad(Si). The testing was performed beyond 100krads(Si) to show trends in device performance as a function of total dose. The test does not classify maximum radiation tolerance of the device, but simply offers designers insight to the critical parameter-shifts up to the specified total dose level.

MIL-STD-883 Method 1019.7 and ASTM F1892-06 were used as guidelines in the development and implementation of the total dose test plan for the MSK7010-3.3HRH.

II. Radiation Source:

Total dose was performed at the University of Massachusetts, Lowell, using a cobalt 60 radiation source. The dose rate was determined to be 114.8 rad(Si)/sec. The total dose schedule can be found in Table I.

III. Test Setup:

All test samples were subjected to Group A Electrical Test in accordance with the device data sheet. In addition, all devices received 160 hours minimum of burn-in per MIL-STD-883 Method 1015. For test platform verification, one control device was tested at 25°C. Nine devices were then tested at 25°C, prior to irradiation, and were found to be within acceptable test limits.

The devices were vertically aligned with the radiation source and enclosed in a lead/aluminum container during irradiation. Four devices were kept under bias during irradiation. An operating voltage of +40 Volts was used for the bias condition. Four devices had all leads grounded during irradiation for the unbiased condition.

After each irradiation, the device leads were shorted together and the devices were transported to the MSK electrical test platform. Testing was performed in accordance with the MSK device data sheet. Testing was performed on irradiated devices, as well as the control device, at each dose level. Electrical tests were completed within one hour of irradiation. Devices were subjected to subsequent radiation doses within two hours of removal from the radiation field.

IV. Data:

All performance curves are averaged from the test results of the biased and unbiased devices respectively. If required, full test data can be obtained by contacting MSK Products – Anaren Inc.

V. Summary:

Based on test data recorded during radiation testing and statistical analysis, the MSK7010-3.3HRH qualifies as a 100KRad(Si) Radiation Hardened device.

Output Voltage linearly decreased by 0.3% up to 150krad(Si), on average under all conditions. Under Voltage Lockout Thresholds and Voltage Lockout Hysteresis also shifted with increasing dose, however remained within specifications.

All other parameters exhibited relative insensitivity to TID, staying well within specifications beyond 150krad(Si).

MSK7010-3.3RH Biased/Unbiased Dose Rate Schedule
--

Dosimetry Equipment
Bruker Biospin # 0162

Irradiation Date
10/11/18

Exposure Length (min:sec)	Incremental Dose rads(Si)	Cumulative Dose rads(Si)
07:29	51,500	51,500
07:29	51,500	103,000
07:29	51,500	154,500

Biased S/N – 0002, 0006, 0009, 0011

Unbiased S/N – 0019, 0020, 0021, 0022

Table 1

Dose Time, Incremental Dose and Total Cumulative Dose

























