

Total Dose Radiation Test Report

MSK5983RH

RAD Hard Positive Adjustable Voltage Regulator

March 20, 2018 (TID, 1st Test

Wafer Lot: HP201682.1 W2)

B. Horton
J. Joy

Anaren, Inc – MSK Products

I. Introduction:

The total dose radiation test plan for the MSK5934RH was developed to qualify the devices as RAD Hard to 100 KRads(Si). The testing was performed beyond 100 KRads(Si) to show trends in device performance as a function of total dose. The test does not classify maximum radiation tolerance of the device, but simply offers designers insight to the critical parameter-shifts up to the specified total dose level.

MIL-STD-883 Method 1019.7 and ASTM F1892-06 were used as guidelines in the development and implementation of the total dose test plan for the MSK5983RH.

II. Radiation Source:

Total dose was performed at the University of Massachusetts, Lowell, using a cobalt 60 radiation source. The dose rate was determined to be 124 rads(Si)/sec. The total dose schedule can be found in Table I.

III. Test Setup:

All test samples were subjected to Group A Electrical Test in accordance with the device data sheet. In addition, all devices received 160 hours minimum of burn-in per MIL-STD-883 Method 1015. For test platform verification, one control device was tested at 25°C. Ten devices were then tested at 25°C, prior to irradiation, and were found to be within acceptable test limits.

The devices were vertically aligned with the radiation source and enclosed in a lead/aluminum container during irradiation. Five devices were kept under bias during irradiation. An operating voltage of +25 Volts was used for the bias condition. Five devices had all leads grounded during irradiation for the unbiased condition.

After each irradiation, the device leads were shorted together and the devices were transported to the MSK electrical test platform. Testing was performed in accordance with the MSK device data sheet. Testing was performed on irradiated devices, as well as the control device, at each dose level. Electrical tests were completed within one hour of irradiation. Devices were subjected to subsequent radiation doses within two hours of removal from the radiation field.

IV. Data:

All performance curves are averaged from the test results of the biased and unbiased devices respectively. If required, full test data can be obtained by contacting MSK Products – Anaren Inc.

V. Summary:

Based on the test data recorded during radiation testing and statistical analysis, the MSK5983RH qualified as a 100 Krad(Si) radiation hardened device. The Set Pin Currents exhibited the most significant change with irradiation, however all performance curves stayed within specification up to 450 Krad(Si) TID.

| |
|---|
| MSK5983RH Biased/Unbiased Dose Rate Schedule |
|---|

| |
|-----------------------|
| Dosimetry Equipment |
| Bruker Biospin # 0162 |

| |
|------------------|
| Irradiation Date |
| 3/20/18 |

| Exposure Length (min:sec) | Incremental Dose rads(Si) | Cumulative Dose rads(Si) |
|---------------------------------|---------------------------------|-----------------------------|
| 6:55 | 51,500 | 51,500 |
| 6:55 | 51,500 | 103,00 |
| 6:55 | 51,500 | 154,500 |
| 20:46 | 154,500 | 309,000 |
| 20:46 | 154,500 | 463,500 |

| |
|---|
| Biased S/N – 0001, 0002, 0003, 0004, 0005 |
|---|

| |
|---|
| Unbiased S/N 0006, 0007, 0008, 0009, 0010 |
|---|

Table 1

Dose Time, Incremental Dose and Total Cumulative Dose











