ASSOCIATION CONNECTING ELECTRONICS INDUSTRIES®	© Co	terial Compo pyright 2005. IPC, Bannoc international and Pan-Ameri	kburn, Illinois	s. All rights reserv	tion with lowe	r level p	arts, the	declarati	on enco	mpasses	all lower	level mate	erials for	which th	e item is an assembly ne manufacturer has leclaration.		
IPC Web Site for Information on IPC-1752 Standard <a href="http://www.ipc.org/IPC-175x">http://www.ipc.org/IPC-175x</a>							Form Type * Distribute			Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materials and Mfg Informa							
Supplier Information																	
Company Name * Company Unique ID				uthority	Respo	onse Date	*		Response Document ID								
Anaren Microwave				2016-	08-11												
Contact Name *	Title - Contact		Phone - Cor	Email	- Contac	t *				<u> </u>	• 11						
Sarvesh Nair		Project Engineer		315-432-890	sarve	sarvesh.nair@anaren.com				uplicate	Contact	-> Autho	orized Re	epresentative			
Authorized Representati	Title - Representative	Э	Phone - Rep	Email	Email - Representative *				Supplier Comments or URL for Additional Information								
Sarvesh Nair		Project Engineer		315-432-8909		sarvesh.nair@anaren.com											
Requester Item Number		Mfr Item Number		Mfr Item Name	Effectiv	ve Date	Version	ersion Manufa		Site	Weight *	UC	OM	Unit Type			
		X3C19F1-03S		3dB Hybrid C	2014-0	07-15	В	East S	Syracuse		0.043	g		Each			
Alternate Recommenda	dation				Alterna			e Item Co	omments								
Manufacturing Proces	ss In	formation		·													
Terminal Plating / Grid Array Material Term			Terminal B	ase Alloy	J-STD-020 MSL Rating		g Peak Process Boo		Body Temperatur		re Max Time at Peak Tem		perature Number of R		of Reflow Cycles		
			CU Alloy	1	2			260			<b>30</b> Se			conds 3			
Comments  Compliant to RoHS 2 Dir	ectiv	ve 2011/65/EU of the	Europear	n Parliament	and of the Coun	cil of 8	June 201	1 & Coi	mmissio	on Delec	nated Dir	ective 20°	15/863/E	EU of 31	March 2015.		

Save the fields in Import fields from a Clear all of the Lock the fields on this **Export Data** Import Data Reset Form Lock Supplier Fields this form to a file file into this form fields on this form form to prevent changes **RoHS Material Composition Declaration Declaration Type \*** Custom Rohs Directive Rohs Definition: Quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury, Hexavalent Chromium, Polybrominated Biphenvls (PBB). Polybrominated Diphenyl Ethers (PBDE) and quantity limit of 0.01% by mass (100 PPM) of homogeneous material for Cadmium 2002/95/EC RoHS 2 (Directive 2011/65/EU & 2015/863/EU) Definition Addendum: Quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Bis(2-ethylhexyl) phthalate (DEHP), Butyl benzyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP). Supplier certifies that it gathered the information it provides in this form concerning RoHS restrictive substances using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its suppliers have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier enter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies provided as part of that agreement, will be the sole and exclusive source of the Supplier's liability and the Company's remedies for issues that arise regarding information the Supplier provides in this form. Supplier Acceptance \* Accepted 1 - Item(s) does not contain RoHS restricted substances per the definition above **RoHS Declaration \*** Exemptions: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions. **Declaration Signature** 

Instructions: Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.

Supplier Digital Signature

## **Homogeneous Material Composition Declaration for Electronic Products**

Subltem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Line Functions: +I Inserts a New Item /SubItem +M Inserts a new Material +C Inserts a new Substance Category +S Inserts a new Substance - Deletes the element line

	Item/SubItem		Homogeneous Material	Weight	Unit of			Level	Substance Category			Substance	CAS	Exempt	'   Weidht	Unit of Measure	Tolerance		PPM
	Name			weight	Measure			Levei				Substance	CAS				-	+	1 1 101
+1 -1	X3C19F1-03S	+M -M	Dielectric	0.0223	g	+C	-C	Supplier		+S	-S	Fiberglass	65997-17-3		0.00625	g			279,94
				•	•	+C	-C	Supplier		+S	-S	Resin	Proprietary		0.0157	g			702,07
						+C	-C	Supplier		+S	-S	Ceramic Filler	Proprietary		0.000401	g			17,975
		+M -M	External Copper	0.00985	g	+C	-c	В	Nickel (external applic	+S	-S	Nickel	7440-02-0		0.000002	g			225
						+C	-C	Supplier		+S	-S	Chromium (Cr) (non-he	7440-47-3		0.000000	g			32
						+C	-c	Supplier		+S	-S	Copper (Cu)	7440-50-8		0.00985	g			999,51
						+C	-C	Supplier		+S	-S	Zinc (Zn)	7440-66-6		0.000002	g			225
		+M -M	Internal Copper	0.011	g	+C	-c	В	Nickel (external applic	+S	-S	Nickel	7440-02-0		0.000002	g			202
		1		1	•	+C	-C	Supplier		+S	-S	Tin (Sn)	7440-31-5		0.000000	g			47
						+C	-C	Supplier		+S	-S	Chromium (Cr) (non-he	7440-47-3		0.000000	g			61
						+C	-C	Supplier		+S	-S	Copper (Cu)	7440-50-8		0.011	g			999,35
						+C	-c	Supplier		+S	-S	Zinc (Zn)	7440-66-6		0.000003	g			330
		+M -M	Tin Plating	0.00005	<b>5</b> g	+C	-c	Supplier		+S	-S	Tin (Sn)	7440-31-5		0.000055	g			1,000,0

Form enabled by Adobe